

## Benefits

- Ideal for home automation systems and as stand alone

## Applications

Automated operation of awning windows, hopper windows, casement windows, curtain wall vents, and skylights.

## Features

- Short-time duty 20% duty cycle
- 24VDC output compact control panel with up to 8A total drive current
- Controls 5 ventilation groups
- Input for external controller (timer)
- Optional connection to rain detectors or wind/rain sensors without any additional modules
- 5-year manufacturer's warranty. Requires reading AFI Install Guide before purchase, and confirmation of project and installation specs by licensed electrical contractor



Enclosure housing sold separately



## GVL 8408-M

Part #	Description
<b>30.209.40</b>	5 Group Control Panel UR
<b>30.209.43</b>	5 Group Control Panel UL

## Specifications

<b>Supply Voltage</b>	120VAC (-15% / +50%)
<b>Output</b>	24VDC / 8A
<b>Dimensions</b>	310mm W x 310mm H x 100mm D (12¼" x 12¼" x 3⅞")
<b>Ambient Oper Temp</b>	-5 °C to +40 °C (23 °F to 104 °F)
<b>Listing</b>	UL Recognized
<b>Protection class</b>	IP50
<b>Typical switch</b>	SPDT Momentary contact (3 leads + ground)
<b>Colors</b>	Plastic: Light Grey RAL 7035

## Accessories

Part #	Description
<b>30.300.90</b>	Rain Detector. IP65. 24VDC
<b>30.301.10</b>	Wind/Rain Sensor. Includes antenna mast mounting.
<b>70.602.17</b>	Programmable Wind/Rain heated sensor

Part #	Description
<b>30.902.20</b>	Thermostat
<b>63.701.29</b>	Control Switch



30.300.90



30.301.10



70.602.17



30.902.20



63.701.29

