

Benefits

- Ideal for smart buildings; integrate with building and home automation systems.

Applications

Automated operation of awning windows, hopper windows, casement windows, curtain wall vents, and skylights.

VCD 204 Actuator Features

- Push/Pull force: 200N (45 lbf)
- Available in Black, White or Silver paint
- 2.5m connection cable with interconnect plug
- TMS+ tandem safety function for operating 2 drives on one sash
- 9.84" (250mm) or 13.78" (350mm) chain operator; Option of chain stroke programmings via magnet
- Programmable drive functions and different drive parameters
- Active closing edge protection (time controlled reversing when an obstacle is detected)
- 5-year manufacturer's warranty. Requires reading AFI Install Guide before purchase, and confirmation of project and installation specs by licensed electrical contractor



Programmable Features

Option of chain stroke programmings via magnet.

| | |
|-------------------------------|--|
| Chain stroke | Up to 350mm (varies by model). |
| Speed reduction | For the last seconds of closing, as a safety precaution. |
| Seal relief adjustment | Between 0-20mm to protect sash at closed position. |

VCD 204

| Part # | Color | Stroke (and force) |
|------------------|--------|--------------------|
| 25.100.05 | Silver | 250mm (200N) |
| 25.100.07 | Black | 250mm (200N) |
| 25.100.06 | White | 250mm (200N) |
| 25.100.05 | Silver | 350mm (200N) |
| 25.100.07 | Black | 350mm (200N) |
| 25.100.06 | White | 350mm (200N) |
| 25.100.00 | | Custom Build |

Specifications

| | |
|------------------------------|--|
| Supply Voltage | 24VDC (-15% / +50%) |
| Nom. Current Draw | Approx 0.35A at 200N load |
| Limit stop | (Open): Built in limit switch (Closed) Integrated electronic power cut-off |
| Chain stroke (approx) | 250mm (9.84") to 350mm (13.78") |
| Push force (Max) | 200N (45 lbf +/- 3%) |
| Pull force (Max) | 200N (45 lbf +/- 3%) |
| Chain speed | 6mm/sec |
| Dimensions | 480mm L x 47mm D x 30mm H (18 ⁷ / ₈ " x 1 ⁷ / ₈ " x 1 ¹ / ₈ ") |
| Run/Rest cycle | For every 60 sec running (on), must then rest (off) for 120 sec |
| Ambient Oper Temp | -10 °C to +60 °C (14 °F to 140 °F) |
| Listing | UL Recognized |
| Protection class | IP30 |
| Colors | Powder-coated: Silver, White, or Black die cast zinc |

