



## Strength & Security for Sliding & Swing Doors

- Provides additional bottom track security locking points
- Recommended for door performance certification testing
- Recommended to use with low profile tracks and thresholds, including FFI low bottom track, FASTrack, FASTrack Drainage and Climatech Threshold
- Concealed within the door bottom rail
- Two click positions,  $\frac{9}{16}$ " &  $\frac{3}{4}$ " for variable sill depths
- For all sash types; for Wood, Vinyl/PVC and Metal doors
- Patent Pending
- Compatible with LAR300 and LAR400 carriages

## Features

- Stainless steel 304 grade for all moving parts
- Minimum bottom rail height:  $2\frac{5}{8}$ "

## Anti-Derailer Lock - Bottom Track Lock

Item #	Description
<b>LLB.01.ASSM</b>	Anti-Derailer kit, 47mm H, $\frac{9}{16}$ " & $\frac{3}{4}$ " throw
	- Lock mechanism      - Access Grommet
	- Mounting Screws      - Strike Keep/Screws
	- Climatech Shim      - Allen Wrench

Questions? We can handle it.

Faster reliable support. Let us show you how.

- We make it easy - CAD drawings, bill of materials, and more
- Samples for Hurricane Testing and other development needs
- In-stock components ready to ship for your just-in-time needs

