

PRODUCT BULLETIN

greenteQ Securitas Offset Twin Cam U-Rail window Espag

greenteQ



Securitas Offset Twin Cam U-Rail Window Espag

The Securitas Offset Twin Cam U-Rail Espag has been designed for use on slim aluminium casement window systems.

It has a 16mm wide U-rail faceplate, so is ideal for systems with no Eurogroove.

Pairs of bi-directional adjustable mushroom headed cams provide compression and security when in the locked position. The cam pairs locate into both sides of a greenteQ night vent striker plate to provide a strong connection.

Securitas Offset has up to 4 pairs of cams depending on the length.

Available in 9 lengths, with cam pairs positioned at each end, fabricators can ensure that locking points are positioned close to the vulnerable corners of their windows.

Securitas Offset is approved for use on Q-secure PREMIUM installations.

The stainless steel U-channel and mushroom cams are very durable, and are covered by the greenteQ 10 year performance guarantee.

Due to the nature of the slim profiles that the espag works on, the gearbox is offset to one edge of the faceplate (hence the name!). This makes the espag handed.

All fixings are applied from one direction, so Securitas Offset is quick and easy to fit.

22mm backset as standard, with 5mm or 7mm mushroom cams, makes Securitas Offset suitable for some of the most popular aluminium systems.

Main Features:

- Available in 9 lengths (300, 400, 600, 800, 900, 1000, 1100, 1200, 1300mm)
- Up to 4 pairs of bi-directional mushroom cams
- 5 and 7mm mushroom heights
- Works with greenteQ night vent strikers
- Stainless steel U-rail faceplate and mushrooms
- All fixings are applied from one direction for ease of fitting
- Works with standard greenteQ Alpha window handles (43mm screw centres and 7mm spindle)
- Q-secure PREMIUM product
- 10 year greenteQ performance guarantee

greenteQ Securitas Offset U-Rail Window Espag

VBH Item Codes

Size (mm)	Handing	22BS 5MB	22BS 7MB	Strikers Required	Box Qty
300	LH	2QWE2701	2QWE2721	2	20
300	RH	2QWE2702	2QWE2722	2	20
400	LH	2QWE2703	2QWE2723	2	20
400	RH	2QWE2704	2QWE2724	2	20
600	LH	2QWE2705	2QWE2725	2	20
600	RH	2QWE2706	2QWE2726	2	20
800	LH	2QWE2707	2QWE2727	2	20
800	RH	2QWE2708	2QWE2728	2	20
900	LH	2QWE2709	2QWE2729	2	20
900	RH	2QWE2710	2QWE2730	2	20
1000	LH	2QWE2711	2QWE2731	3	20
1000	RH	2QWE2712	2QWE2732	3	20
1100	LH	2QWE2713	2QWE2733	3	20
1100	RH	2QWE2714	2QWE2734	3	20
1200	LH	2QWE2715	2QWE2735	4	20
1200	RH	2QWE2716	2QWE2736	4	20
1300	LH	2QWE2717	2QWE2737	4	20
1300	RH	2QWE2718	2QWE2738	4	20

Dimensions (mm)

Size	Dim A	Dim B	Dim C	Dim D	Dim E	Dim F
300	320	111	111	79	-	-
400	420	161	161	79	-	-
600	620	261	261	79	-	-
800	820	361	361	79	-	-
900	920	411	411	79	-	-
1000	1020	461	461	79	170	-
1100	1120	511	511	79	170	-
1200	1220	561	561	79	170	170
1300	1320	611	611	79	170	170

